

**PRECAUTIONARY STATEMENTS: HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

DANGER. CORROSIVE. CAUSES SEVERE EYE AND SKIN DAMAGE. HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. Do not get in eyes, on skin or on clothing. Wear goggles or face shield, rubber gloves when handling. Keep away from heat and open flame. Keep container closed when not in use. Avoid breathing of vapor. Use with adequate ventilation. Do not take internally.

**ENVIRONMENTAL HAZARDS**

This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**STORAGE AND DISPOSAL**

**STORAGE:** Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. Do not reuse empty container.

**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL**

**METAL CONTAINERS:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

**PLASTIC CONTAINERS:** Do not reuse empty container. Triple rinse (or equivalent). Then puncture and dispose of in a sanitary landfill, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.



**8256  
FUEL OIL TREATMENT**

**ACTIVE INGREDIENT:**

1-(2-hydroxyethyl)-2-alkyl (C <sub>18</sub> )*-2-imidazoline.....	25.0%
<b>INERT INGREDIENTS:</b> .....	<u>75.0%</u>
<b>Total</b> .....	<b>100.0%</b>

\*As in Tall Oil Fatty Acids

**KEEP OUT OF REACH OF CHILDREN  
DANGER**

**FIRST AID**

- **IF IN EYES:** Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control center or doctor for treatment advice.
- **IF SWALLOWED:** Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told by a poison control center or doctor.
- **IF ON SKIN:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
- **IF INHALED:** Move person to fresh air. If person is not breathing, call 911 or ambulances, then give artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for treatment advice
- Have the MSDS with you when calling a poison control center or a doctor, or going for treatment.

**NOTE TO PHYSICIAN:** Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

EPA Reg. No. 68708-3

EPA Est. No. 68708-TX-1

ONDEO NALCO ENERGY SERVICES  
7701 HWY 90A  
SUGAR LAND, TEXAS 77478  
EMERGENCY TELEPHONE NUMBER (800) 424-9300

**DIRECTIONS FOR USE**

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

**FOR USE WITH  
CLOSED DELIVERY SYSTEMS ONLY**

To inhibit sludge formation, to disperse existing sludge and to control filter - plugging bacteria and fungi in fuel oil storage tanks and feed lines, use 0.04 to 0.08 gallons of 8256 Fuel Oil Treatment per 1000 gallons of fuel oil [5.1 to 10.2 ounces/1000 gallons](40 to 80) ppm. Higher dosage may be required to completely inhibit some bacteria not considered to be factors in filter plugging.

Feed 8256 Fuel Oil Treatment by means of proportioning pump or siphon type feeder directly from drum or other container to the fuel oil as it is pumped into storage tanks.

**NOTE: 8256 FUEL OIL TREATMENT IS INTENDED FOR INDUSTRIAL USE ONLY.**

**Net Contents Shown Elsewhere On Container**