

BEFORE HANDLING OR USING, READ AND UNDERSTAND
CURRENT MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT.

FIRST AID

If in Eyes: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
If on Skin or Clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
If Swallowed: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person.
If Inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.
FOR EMERGENCY MEDICAL INFORMATION,
CALL 1-800-328-0026.
Have the product container or label with you when calling a poison control center or doctor, or going for treatment.
NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. Do not contaminate water when disposing of equipment washwaters.
Instructions in Case of Spills or Leaks: Wear goggles, rubber gloves, and protective clothing. Absorb spills and leaks with inert material such as sand, clay or vermiculite. Shovel into a sealable container and dispose of in an authorized EPA disposal facility.
In Case of Fire: Use water, carbon dioxide, dry chemical (e.g. Sodium bicarbonate) extinguishing medias. Fire fighters should be equipped with self-contained breathing apparatus and turnout gear.



NOTICE
Do Not Ship or Store
with Food, Feeds, Drugs,
or Clothing

BATCH NUMBER: _____

Item Code: 00000

xxxxxx/2700/xxxx

A-245

COMMERCIAL MICROBIOCIDES

**A BROAD SPECTRUM MICROBICIDE FOR CONTROLLING SLIME-FORMING
AND SULFATE-REDUCING BACTERIA, FUNGI, YEAST AND ALGAE.
FOR USE IN AIR WASHERS AND INDUSTRIAL SCRUBBING SYSTEMS;
RECIRCULATING COOLING AND PROCESS WATER SYSTEMS; HEAT
TRANSFER SYSTEMS; SERVICE WATER AND AUXILIARY SYSTEMS;
INDUSTRIAL WASTEWATER SYSTEMS INCLUDING WASTEWATER
SLUDGE AND HOLDING TANKS**

ACTIVE INGREDIENT:

Glutaraldehyde.....	45.0%
INERT INGREDIENTS:	55.0%
TOTAL	100.0%

KEEP OUT OF REACH OF CHILDREN DANGER

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CORROSIVE. Causes irreversible eye damage. Causes skin irritation. Harmful if inhaled, swallowed or absorbed through the skin. May cause allergic skin reactions. Causes asthmatic signs and symptoms in hyper-reactive individuals. Do not get in eyes, on skin or on clothing. Avoid breathing vapors. Not to be used as an aerosol. Do not swallow. Wear eye goggles, rubber gloves and protective clothing. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.
Pesticide Storage: A-245 solutions are corrosive to many commonly used materials of construction such as steel, galvanized iron, aluminum, tin and zinc. These solutions can be stored and handled in baked phenolic lined steel, stainless steel or reinforced epoxy equipment. This product freezes at approximately -20°C (-4°F). Therefore, unless the storage tank is inside or underground, heating and insulation may be required. If heating is needed, exposure to high temperatures should be avoided. For short storage (1 month) temperatures up to 100°F can be tolerated; however, the preferred maximum storage temperature is approximately 80°F. Keep away from fire and open flames. A stainless steel centrifugal pump is suggested for transfer service.
Pesticide Disposal: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or your Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.
Container Disposal: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.
EPA Reg. No: 1677-206
EPA Est. 1677-MN-1(P), 1677-CA-2(R), 1677-TX-1(D), 1677-OH-1(H), 1677-IL-1(J), 1677-GA-1(M), 1677-PR-1(B), 1677-CA-1(S), 1677-WV-1(V), 1677-IL-2(J)
Superscript refers to first letter of date code.

Manufactured by
Ecolab Inc., Water Care Services
370 Wabasha Street North
St. Paul, MN 55102 Made in U.S.A.

CONTAINER SIZE: 55 GALLONS/208 LITERS

NET CONTENTS: 504 lb/229.1 kg

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

GENERAL USE DIRECTIONS

Add A-245 at a point of uniform mixing where the treated water will be circulated or mixed throughout the system. Badly fouled systems should be cleaned before treatment begins. A-245 can be applied either intermittently (slug dose) or by continuous feed where stated. Where appropriate, feed points should be below the water line to minimize vapor.

AIR WASHERS AND INDUSTRIAL SCRUBBING SYSTEMS, RECIRCULATING COOLING AND PROCESS WATER SYSTEMS

Use only in industrial air washer systems, which have mist-eliminating components. Badly fouled systems can be shock treated by using the highest recommended rate of A-245. Under these conditions, blowdown should be discontinued for up to 24 hours. Apply by intermittent or continuous feed methods. Add at a place such as the basin area.

Initial Dose: When the system is noticeably fouled, add 12.8-25.6 fl. oz. (111-222 ppm) of A-245 per 1,000 gal. of water in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 5.1-12.8 fl. oz. (44-111 ppm) of A-245 per 1,000 gal. of water in the system per day, or as needed to maintain control.

Not for use in industrial scrubbing systems in the State of California.

HEAT TRANSFER SYSTEMS

For use in Evaporative Condensers, Dairy Sweetwater Systems, Hydrostatic Sterilizers and Retorts and Pasteurizers and Warmers, and Once-Through Cooling Water Systems.

Initial Dose: When the system is noticeably fouled, add 12.8-25.6 fl. oz. (111-222 ppm) of A-245 per 1,000 gal. of water in the system.

Subsequent Dose: For maintenance, use a continuous feed of 5.1-12.8 fl. oz. (44-111 ppm) of A-245 per 1,000 gal. of water in the system per day.

Not for use in Dairy Sweetwater Systems and Once-Through Cooling Water Systems in the State of California.

SERVICE WATER AND AUXILIARY SYSTEMS

Use in systems such as fire water reserves, spray paint booths and emergency cooling water systems. Dose initially at 12.8-25.6 fl. oz. (111-222 ppm) of A-245 per 1,000 gal. of water in the system.

Reapply as necessary to maintain this concentration.

Not for use in the State of California.

INDUSTRIAL WASTEWATER SYSTEMS

For use in aerobic and anaerobic, belt pressed, digested and undigested sludges; and holding tanks. Add 0.56 to 2.56 gal. (500 to 2,000 ppm) of A-245 per 1,000 gal. of wastewater or sludge. Not for use in the State of California.

CONDITIONS OF SALE

The Directions for Use of this product reflect the opinion of experts based on field use and tests. The directions are believed to be reliable and should be followed carefully. However, it is impossible to eliminate all risk inherently associated with use of this product. Ineffectiveness or other unintended consequences may result because of such factors as weather conditions, presence of other materials, or use of the product in a manner inconsistent with its labeling, all of which are beyond the control of the Seller. All such risks shall be assumed by the Buyer. The manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes referred to above. THE MANUFACTURER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS OR MERCHANTABILITY OR ANY OTHER EXPRESS OR IMPLIED WARRANTY. IN NO CASE SHALL THE MANUFACTURER BE LIABLE FOR CONSEQUENTIAL, SPECIAL OR INDIRECT DAMAGES RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT. The manufacturer offers this product, and the Buyer and User accept it, subject to the foregoing Conditions of Sale and Warranty which may be varied only by agreement in writing signed by a duly authorized representative.