

File: 6000 os9  
Trim

trim margins at 10.25", 6.75", 6 finished label 6" high

# 6000

ACTIVE INGREDIENT(S)		
4-(2-Nitrobutyl)morpholine	81% by wt	
4,4'-(2-Ethyl-2-nitrotrimethylene)dimorpholine	5% by wt	
Inert Ingredients	14% by wt	
Total	100%	

**KEEP OUT OF REACH OF CHILDREN**

## DANGER

FIRST AID	
<b>If in Eyes</b>	- Hold eye open and rinse slowly and gently with water for 15-20 minutes. - Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes. - Call a poison control center or doctor for further treatment advice.
<b>If Swallowed</b>	- Call poison control center or doctor immediately for treatment advice. - Have person sip a glass of water, if able to swallow. - Do no induce vomiting unless told to do so by poison control center or doctor.
<b>If on Skin</b>	- Take off contaminated clothing. - Rinse skin immediately with plenty of water for 15-20 minutes. - Call a poison control center or doctor for treatment.
<b>If Inhaled</b>	- Move person to fresh air. - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible. - Call a poison control center or doctor for further treatment.
HOT LINE NUMBER	
<b>IN CASE OF AN EMERGENCY</b> endangering life or property involving this product, call <b>1-800-424-9300</b> . Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment.	
<b>NOTE TO PHYSICIAN:</b> Probable mucosal damage may contraindicate the use of gastric lavage.	

### PRECAUTIONARY STATEMENTS

#### Hazards to Humans and Domestic Animals

**CAUSES SEVERE EYE DAMAGE AND SKIN BURNS. MAY CAUSE ALLERGIC SKIN REACTION. HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH THE SKIN.**

Do not get in eyes, on skin, or on clothing. Causes skin sensitization. Wear goggles or face shield and rubber gloves when handling. Wash thoroughly after handling. Avoid breathing vapor or mist. Avoid contamination of food. Do not take internally.

#### ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**Pesticide Disposal:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**Container Disposal:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by other procedures approved by state and local authorities.



#### DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

**FOR USE IN HYDROCARBON PRESERVATION**  
**To control the growth of problem microorganisms associated with the fuel.**

**In general use.** Add 6000 to storage tanks or fuel tanks for control of microbial growth in diesel oil, fuel oil, gasoline, or kerosene. Treatment may be performed by slug dosage or by intermittent metering to attain a concentration of 135-1000 ppm of 6000.

**For storage above water.** Add 1 gallon of 6000 to each 1000 gallons of water in the bulk storage system to achieve a concentration of approximately 1000 ppm. To facilitate mixing, dissolve each gallon of 6000 in 100 gallons of water and add this solution directly to the water phase in the tank with minimal agitation.

**For storage in tanks without intentional water.** Add 0.125-1 gallon of 6000 directly to each 1000 gallons of hydrocarbon in the system to obtain a concentration of approximately 135-1000 ppm.

**In a fuel-treatment pre-mix.** 6000 may be mixed with other fuel additive for addition to fuel. The end user must add sufficient 6000 to the pre-mix to provide 135-1000 ppm of 6000 in the treated fuel.

**Distributed by: Innospec Fuel Specialties LLC**

8375 South Willow Street, Littleton, Colorado 80124,  
(303) 792-5554 or 1-800-441-9547

**Product Information: 800-441-9547**

EPA Reg. No.  
464-659-68827

EPA Est. No.  
73583-TX-1

Last Revision 9/13/06

**Net Contents: 1 gallon**

Lot#

**Notice :** Seller warrants that the product conforms to its chemical description as contained on this label and is reasonably fit for the purposes stated on this label (except uses for which USEPA has accepted the required data and/or citations of data the formulator has submitted in support of registration) when used in accordance with directions under normal condition of use. THE WARRANTIES MADE IN THIS PARAGRAPH ARE SELLER'S SOLE WARRANTIES WITH RESPECT TO THE PRODUCT AND ARE MADE EXPRESSLY IN LIEU OF AND EXCLUDE ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER EXPRESS OR IMPLIED REPRESENTATIONS AND WARRANTIES.